

Compatible with a wide range of measurement of various particle sizes and types



# Liquid-Borne Particle Sensor KS-42C

- Detects particles down to 0.5  $\mu\text{m}$  size, at a flow rate of 10 mL/min
- Up to 10 user selectable channels (by KE-40B1) from 0.5  $\mu\text{m}$  to 20  $\mu\text{m}$   
Factory default setting : seven channels ( $\geq 0.5 \mu\text{m}$ ,  $\geq 1 \mu\text{m}$ ,  $\geq 2 \mu\text{m}$ ,  $\geq 3 \mu\text{m}$ ,  $\geq 5 \mu\text{m}$ ,  $\geq 10 \mu\text{m}$ ,  $\geq 20 \mu\text{m}$ )
- Integrated leak sensor with alarm output




## Specifications [KS-42C]

Optical system	Light-scattering method
Light source	Laser diode (wavelength 780 nm, rated output 5 mW)
Laser product class	Class 1, IEC 60825-1
Light detector	PIN type photodiode
Materials of parts exposed to sample	Synthetic quartz, PFA, PTFE
Allowable sample type	Any liquid that does not corrode contacting materials
Calibration	Polystyrene latex (PSL) particles (refractive index 1.6) in pure water
Size range	
7 channels (factory default)	≥0.5 μm, ≥1 μm, ≥2 μm, ≥3 μm, ≥5 μm, ≥10 μm, ≥20 μm
User selectable channels	1 channel to 10 channels, setting made from Controller
Setting range	0.5 μm to 20 μm
Counting efficiency	70 % to 110 %
Flow rate	10 mL/min
Maximum particle number concentration	1 200 particles/mL (at 5 % coincidence loss for 0.5 μm particles)
Sample pressure range	300 kPa (gauge pressure) or less
Sample inlet/outlet	2 (dia.) x 4 (dia.) flared joint for tube
Purge air port	Rc1/8 (1/8 PT female screw)
Input/output connector	
CONTROLLER connector	Connecting to KE-40B1
LIQUID LEAK	Alarm output terminal shorted during normal operation, open when internal leak is detected
ALARM connector	
Power	DC12 V (supplied by KE-40B1)
Environmental conditions for operation	+15 °C to +35 °C, less than 80 % RH (no condensation)
Dimensions and weight	125 (H) x 240 (W) x 151 (D) mm (excluding protrusions), Approx. 3 kg
Accessories	Tube A vacuum pack x 1 (2 x 4 dia. PFA tube with flared joint at one end, 1.5 m x 2, Union joint x 1), Connection cable A (1 m) x 1

Option Connection cable (5 m) KS-42-123

## Example of measuring system




## RP Monitor Evo10 K1701 Ver.2

Option

Used for controlling particle counters to regulate the start/end of measurement and turn the light source/built-in pump on and off. Available setting parameters include measurement time, period, number of measurements, alarm, and conversion.

- Allows control of up to 8 particle counters in serial mode, using 8 ports.
- Operating system: Microsoft Windows 10 Pro 64 bit / 11 Pro 64 bit



Sample display

## Syringe Sampler KZ-31W

For batch measurement of liquid-borne particle sensor.

\*Connecting cable (KZ30S180, option)



For operation control of particle sensor and display of measurement data

## Controller KE-40B1

- Particle size range can be freely set for up to 10 channels.
- Built-in printer. Measurement data can be stored on memory card (CF card).



## Specifications [KE-40B1]

Display	
Display items	Particle size range (max.10 channels), Count (max. 8 digits)
Controls	Touch panel, Sheet switches
Measurement	
Measurement time	10 seconds to 2 hours, or manual
Measurement modes	Manual measurement Automatic measurement: mean value measurement, moving average measurement, periodic measurement, scheduled time measurement
Alarm	When measured value in a selected channel reaches the preset alarm level, a buzzer sounds and alarm terminals are shorted by relay contacts Maximum connected load: DC 30 V, 1 A
Communication	RS-232C
Printer	Printout of measurement results, date and time
Recording paper	Thermal paper: TP-08, Clean thermal paper: TP-10
Memory	CompactFlash (CF) card®(automatic storage in TSV format )
Power	100 to 240 V AC, 50/60 Hz, approx. 130 VA
Dimensions and weight	140 (H) x 240 (W) x 146 (D) mm (excluding protruding parts), approx. 3 kg
Accessories	Power cord x 1, Thermal paper TP-08 x 2 rolls
Options	Communication cable CC-61A/63A, Thermal paper TP-08, Lint-free thermal paper TP-10, Memory card MC-25CF2 (256 MB)
Factory option	D/A converter interface KE-40-S06

\*Use only RION supplied cards for assured operation.

\* Company names and product names mentioned in this catalog are usually trademarks or registered trademarks of their respective owners.  
\* Specifications subject to change without notice.

Distributed by:

 **RION CO., LTD.**  
<https://www.rion.co.jp/english/>

3-20-41, Higashimotomachi, Kokubunji,  
Tokyo 185-8533, Japan  
Tel: +81-42-359-7878, Fax: +81-42-359-7445